



886 200 A4

Biegeradius min. dauernd
Min. bend radius for flexing 48mm



Biegeradius min. einmalig
Min. bend radius for rigid configuration 18mm

Schleppkettenradius min.
Min. drag chain radius --

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps
For max. cable length (L): See Specifications of the encoder model

Toleranztabelle	
L	T
<= 250mm	± 5mm
< 1000mm	+ 10mm
<= 3000mm	+ 30mm
> 3000mm	+ 1%

			IDnumber:
			Change No. C062923-1 Phase: Serie
	Original drawing Scale	Format	AGK JAE --> abgeschnittenes Ende (1H 6, Anschlussmaße
Dimensions in mm	1:1	A4	
			Tolerierung nach DIN ISO 8015 Tolerances as per DIN ISO 8015
			Allgemeintoleranzen ISO 2768-mH ±6mm: +- 0,2 General tolerances ISO 2768-mH ±6mm: +- 0,2
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)			
HEIDENHAIN DR. JOHANNES HEIDENHAIN GmbH 83301 Traunreut, Germany		Version	Revision
		Sheet	
		D 1231810 - 00 - B - 02	
		Document number	
		1 of 1	