



Biegeradius min. dauernd
Min. bend radius for flexing 36mm

Biegeradius min. einmalig
Min. bend radius for rigid configuration 14mm

Schleppkettenradius min.
Min. drag chain radius --

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps
For max. cable length (L): See Specifications of the encoder model

Toleranztabelle	
L	T
≤ 250mm	± 5mm
< 1000mm	+ 10mm
≤ 3000mm	+ 30mm
> 3000mm	+ 1%

			IDnumber:
			Change No. C062923-1 Phase: Serie
			Tolerierung nach DIN ISO 8015 Tolerances as per DIN ISO 8015
			Allgemeintoleranzen ISO 2768-mH ±6mm: +- 0,2 General tolerances ISO 2768-mH ±6mm: +- 0,2
	Original drawing Scale	Format	AGK JAE --> abgeschnittenes Ende Schirm
Dimensions in mm	1:1	A4	Anschlussmaße

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. (ISO 16016)

HEIDENHAIN
DR. JOHANNES HEIDENHAIN GmbH
83301 Traunreut, Germany

	Version	Revision	Sheet	
D 1231810 - 00 - C - 03				1 of 1
Document number				