



Biegeradius min. dauernd  
Min. bend radius for flexing 48mm

Biegeradius min. einmalig  
Min. bend radius for rigid configuration 18mm

Schleppkettenradius min.  
Min. drag chain radius --

max. Kabellänge (L): siehe Techn. Daten des Gerätetyps  
For max. cable length (L): See Specifications of the encoder model

| Toleranztabelle |        |
|-----------------|--------|
| L               | T      |
| ≤ 250mm         | ± 5mm  |
| < 1000mm        | + 10mm |
| ≤ 3000mm        | + 30mm |
| > 3000mm        | + 1%   |

886 200 A4

|                  |                  |                                         |                                                                                             |
|------------------|------------------|-----------------------------------------|---------------------------------------------------------------------------------------------|
|                  |                  |                                         | IDnumber:                                                                                   |
|                  |                  |                                         | Change No. C062923-1<br>Phase: Serie                                                        |
|                  |                  |                                         | Tolerierung nach DIN ISO 8015<br>Tolerances as per DIN ISO 8015                             |
|                  |                  |                                         | Allgemeintoleranzen ISO 2768-mH ±6mm: +- 0,2<br>General tolerances ISO 2768-mH ±6mm: +- 0,2 |
|                  | Original drawing | AGK JAE --> abgeschnittenes Ende Schirm |                                                                                             |
|                  | Scale            | Anschlussmaße                           |                                                                                             |
|                  | Format           |                                         |                                                                                             |
| Dimensions in mm | 1:1              | A4                                      |                                                                                             |

The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited. Offenders will be held liable for the payment of damages. All rights reserved in the event of the grant of a patent, utility model or design. ( ISO 16016 )

**HEIDENHAIN**  
DR. JOHANNES HEIDENHAIN GmbH  
83301 Traunreut, Germany

|                         |         |          |       |        |
|-------------------------|---------|----------|-------|--------|
|                         | Version | Revision | Sheet |        |
| D 1231810 - 00 - C - 04 |         |          |       | 1 of 1 |
| Document number         |         |          |       |        |